



OC ASIAN
CONCRETO
BEAUTIFY YOUR WAY



ASIAN HOLLOW BLOCK

Concrete Blocks



ASIAN HOLLOW BLOCK

Stronger. Lighter. Better.

Asian Hollow Blocks are Concrete Blocks from the house of Asian Concrete with two or more hollow cavities that can be further reinforced making them the ideal material to build both load-bearing and non-load bearing wall structures.

Asian Hollow Blocks provides structures with augmented strength and stability, and has minimum environmental impact.

Special Features:

- Manufactured in 100% Automated Plant with technology from Germany
- Superior finish
- Excellent sound and thermal insulation
- Lower density and weight
- Pre-cured
- Minimum breakage and wastage

Where to be used:

Where to be used: Fair Face Walls | Partitioning Walls | Load Bearing Walls | Boundary Walls | Decorative Application

Colour Range:




Specifications:

Parameters	Dimensions
Hollow Block (in)	4 / 6 / 8
Length (mm)	390
Height (mm)	190
Thickness (mm)	100 / 150 / 200
Blocks/m ²	13.49
Compressive Strength (N/mm ²)	≥ 7.5
Blocks/sqft	1.25


8" Hollow Blocks



6" Hollow Blocks



4" Hollow Blocks



Advantages:

- **Rapid Execution of Work:** Asian Hollow Blocks are lighter and of uniform size. This facilitates rapid execution.
- **Increase in Floor Area:** Option to build thinner walls helps save space and increase floor area.
- **Reduces Construction Cost:** Asian Hollow Blocks helps save construction material and reduces construction cost.
- **Better Insulation:** Offers great insulation against sound, heat and dampness.
- **More Durable:** Asian Hollow Blocks withstands atmospheric turmoil and requires no protective covering.
- **Bonding of Mortar & Plaster:** Rough surface provides good bonding of mortar and plaster.
- **Cost-Effective:** The block's durability and great strength reduce maintenance cost.

ASIAN CONCRETO PVT. LTD.



INDIA SALES OFFICE:
Plot No. 84, Palm Paradise, Ramgarh Taal, Gorakhpur, UP, India
Phone: +91-8127585858

NEPAL SALES OFFICE:
1st Floor, ShriPri Home, Kalikasthan - 29, Kathmandu, Nepal
Phone: +977-9802711199

FACTORY:
Ramgram - 16
Nawalparasi, Nepal.
Phone: +977-9802711199

Email: info@asianconcreto.com
Website: www.asianconcreto.com
Follow us on [f](#) [@](#) [v](#) [i](#)
Asian Concrete Pvt. Ltd.

Technical Specification of Concrete Masonry Unit (Hollow Block)

Product : Hollow Block (390x100x190)mm
Hollow Block (390x150x190)mm
Hollow Block (390x200x190)mm

S.No.	Description	Asian Concrete			Standard References
					IS 2185(Part 1), NS 119
1	Dimension of Specimen				
	Length mm	390	390	390	As per Actual
	Width mm	100	150	200	As per Actual
	Height mm	190	190	190	As per Actual
2	Dimension Tolerance				
	Length mm	± 1mm	± 1mm	± 1mm	± 5mm
	Width mm	± 1mm	± 1mm	± 1mm	± 3mm
	Height mm	± 2mm	± 2mm	± 2mm	± 3mm
3	Surface Area				
	cm ²	390	585	780	As per Actual
4	Volume of Specimen				
	cm ³	7410	11115	14820	As per Actual
5	Minimum Compressive Strength N/mm²				
	28 Days	≥ 7.5	≥ 7.5	≥ 7.5	Minimum 5N/mm ²
6	Thickness of Face Shell				
	mm	28	28	28	(390x100x190)mm = 25mm Min (390x150x190)mm = 25mm Min (390x200x190)mm = 30mm Min
7	Thickness of Web				
	mm	28	28	28	(390x100x190)mm = 25mm Min (390x150x190)mm = 25mm Min (390x200x190)mm = 25mm Min
8	Water Absorption				
	(%)	< 8%	< 8%	< 8%	Maximum 10%
9	Drying Shrinkage				
	(%)	< 0.04	< 0.04	< 0.04	Maximum 0.04%
10	Moisture Movement				
	(%)	< 0.03	< 0.03	< 0.03	Maximum 0.03%
11	Dry Density				
	kg/m ³	1600	1600	1600	1600 kg/m ³
12	Lable and Marking				
	Concrete hollow block package shall be marked with the following information suitably:				
	a) Identification of the manufacturer,				
	b) Grade of hollow blocks, and				
	c) Date of manufacture.				
Note: The product should be adequately packed to identify above and also ensure products from manufacturer facility to the buyer facility during loading transport, unloading do not suffer any physical damage including chipping, cracking, deform or any other damage from actual product specifications					