

The image features a background of various colored paving stones (red, grey, blue, and yellow) arranged in circular patterns. The stones are shown in several overlapping circular cutouts. The logo for Asian Concrete is positioned in the top right corner. The logo consists of a stylized 'CC' symbol in black and orange, followed by the word 'ASIAN' in large, bold, black letters. Below 'ASIAN' is the word 'CONCRETO' in orange letters, and at the bottom of the logo is the tagline 'BEAUTIFY YOUR WAY' in smaller, black, uppercase letters.

**CC ASIAN**  
**CONCRETO**  
BEAUTIFY YOUR WAY

**ASIAN NOSTALGIC**

Nostalgic Paving Stone

# ASIAN NOSTALGIC

## Nostalgic Paving Stone

Nostalgic Rings are true copy of European Ethnic Design Pattern in single or color combination. The individual pieces are sized in such a way the various sizes of circular designs can be achieved as per your requirements.

### Special Features:

- Manufactured in 100% Automated Plant with technology from Germany
- Cured in heat and humidity controlled curing chamber
- Dust and slush-free, aesthetically pleasant surroundings
- Excellent skid resistance

### Advantages:

- Quick and easy, year round installation
- Simple and reusable
- Cost-effective, less time-consuming

### Where to be used:

Sidewalks | Walkways | Parks | Patios | Landscaping


### Description and Details:

No. of pieces in one set: 104 pcs.

Area covered by one set: 1.09 m<sup>2</sup>/ 0.10 ft<sup>2</sup>

Compressive strength: ≥ 45 N/mm<sup>2</sup>

### Colour Range:



### Specifications:

Parameters	Dimensions
Length (mm)	1157
Width (mm)	944
Thickness (mm)	60
Coverage Area Per Set (m <sup>2</sup> )	1.09
Coverage Area Per Set (ft <sup>2</sup> )	0.10
Compressive Strength (N/mm <sup>2</sup> )	≥ 45

### Load Factor:



ASIAN CONCRETO PVT. LTD.



**INDIA SALES OFFICE:**  
Plot No. 84, Palm Paradise, Ramgarh Taal, Gorakhpur, UP, India  
Phone: +91-8127585858

**NEPAL SALES OFFICE:**  
1st Floor, ShriPri Home, Kalikasthan - 29, Kathmandu, Nepal  
Phone: +977-9802711199

**FACTORY:**  
Ramgram - 16  
Nawalparasi, Nepal.  
Phone: +977-9802711199

Email: [info@asianconcreto.com](mailto:info@asianconcreto.com)  
Website: [www.asianconcreto.com](http://www.asianconcreto.com)  
Follow us on [f](#) [i](#) [y](#) [in](#)  
Asian Concreto Pvt. Ltd.

## Technical Specification of Precast Concrete Pavers (Paving Block)

**Product : Nostalgic Paver (1157x944x60)mm Per Set**

S.No.	Description	Asian Concrete	Standard References
			<i>Nepal Standard 593:2077</i>
1	<b>Dimension of Specimen</b>		
	Length mm	1157	As per Actual
	Width mm	944	As per Actual
	Thickness mm	60	As per Actual
	Aspect Ratio mm	Not Defined	Maximum 4
	Arris/ Chamfer mm	Rounded	Min 5, Max 7
	Squareness mm	Nil	Nil
	Thickness of Wearing Layer mm	> 6	Minimum 6mm
2	<b>Dimension Tolerance</b>		
	Length mm	± 1mm	± 2mm
	Width mm	± 1mm	± 2mm
	Thickness mm	± 1mm	± 1mm
	Squareness mm	± 0mm	± 2mm
	Thickness of Wearing Layer mm	(+) 2mm	(+) 2mm
	Chamfer mm	± 0mm	± 1mm
3	<b>Surface Area of Paver</b>		As per Actual
	cm <sup>2</sup>	10922	
4	<b>Volume of Specimen</b>		As per Actual
	cm <sup>3</sup>	65532	
5	<b>Minimum Compressive Strength N/mm<sup>2</sup></b>		35 N/mm <sup>2</sup>
	28 Days	≥ 35	
6	<b>Water Absorption</b>		Maximum 6%
	(%)	< 6%	
7	<b>Dry Density</b>		2250 kg/m <sup>3</sup> , ± 50 kg/m <sup>3</sup>
	kg/m <sup>3</sup>	2250	
8	<b>Abrasion Resistance</b>		Maximum 3mm
	mm	< 2mm	
9	<b>Face Layer Pigment (Color)</b>	Synthetic or Natural	Synthetic or Nautral (Zinc compound or organic dyes or Lead pigments shall not be used)
10	<b>Lable and Marking</b>		
	Concrete paver block package shall be marked with the following information suitably:		
	a) Identification of the manufacturer,		
	b) Grade of paver blocks, and		
	c) Date of manufacture.		
Note: The product should be adequately packed to identify above and also ensure products from manufacturer facility to the buyer facility during loading transport, unloading do not suffer any physical damage including chipping, cracking, deform or any other damage from actual product specifications			